

**PERFIX INC.**

# INSTALLATION INSTRUCTIONS FOR LOCKERS

Made in Canada

## INSTALLATION PLAN.

- Follow the installation drawings as described in the architecture's plans with regards to the sites and the quantities where the lockers are required.
- Take measurements of the site.

## **WALL INSTALLATION**

1. According to the number of rows necessary, fix the recess bases to the floor on level, according to the usual methods. (Picture #1)
  2. Place the lockers on the bases (Picture #2) and fix them one at the other. (Picture #7)
- N.B.: To install a single unit apart, squares of 1" X 1" must be fixed at the base in order to fix the locker at this one.
3. Fix the lockers to the wall in the solid amounts or other places. (Picture #3). If needed, fix the lockers at the bases (3" screws minimum).
  4. When necessary, install the sloping tops the numbering plates and all other accessories.
  5. Before a last inspection, if required adjust the doors and the hasps.

\*N.B.: For fixings, if possible drill where there are 2 thicknesses of metal such as the back and frame, this will increase the solidity of the installation.

## **BACK TO BACK INSTALLATION (ISLANDS)** (Picture #4)

**\*Check general alignment particularly. Leave a minimum of 48" of space between each row for 12" width lockers.**

1. Before fixing the bases at the floor on level, those must be joined between them. (Picture #5). Insert steel plates between the bases by taking care to let them exceed (Picture #5) in order to fix the back of the locker at the base (Picture #6). Each block of lockers must be fixed firmly one to the other, aligned well and on level. (Picture #7).
2. If needed, steel plates can be fixed above the lockers to solidify the installation in islands (back to back).
3. Fix the lockers at the bases (3" screws minimum). (Picture #8). Repeat items 4 and 5 of the installation to the wall.

## **INSTALLATION OF THE SLOPING TOPS**

1. Put the supports on the tops of the lockers at all separations of the blocks of lockers. (Picture #9)
2. Place the sloping tops on the supports.
3. Insert the cover-joints (slot) in the tops. (Picture #10)
4. Fix the obturators at the end of the lines on the sides of the lockers.
5. Fix the cover-joints, obturators and the sloping top corners with the front frame of the lockers. (Picture #11)

## **ANCHORING – Manufacturer's suggestion**

Anchor bolts (concrete) ¼" X 1 ¼" or 1" Ramset nail of (Pictures #1 and 3)  
 Rivets 1/8" X ¼" (Pictures #5,6,7,10 and 11) Rivets 3/16" X ¼" (Picture #7)  
 #8 screws – 3" (Picture #8), #8 screws – 2" (Picture #3)



No 1



No 3



No 2



No 4



No 6



No 8




No 10



No 5



No 7



No 9



No 11